

Printed Pages—4

ECE011

(Following Paper ID and Roll No. to be filled in your Answer Book)

PAPER ID :100651

Roll No.

| | | | | | | | | | |
|--|--|--|--|--|--|--|--|--|--|
| | | | | | | | | | |
|--|--|--|--|--|--|--|--|--|--|

B.Tech.

(SEM. VI) THEORY EXAMINATION 2013-14

ADVANCED FOUNDATION DESIGN*Time : 2 Hours**Total Marks : 50***Note :—Attempt all questions**

1. Attempt any **four** parts of the following : **(3.5×4=14)**
- (a) Discuss the equivalent point load method based on approximate stress distribution.
 - (b) State Boussinesq's equation for determining the vertical pressure under a superimposed load. Discuss the limitations of the equation.
 - (c) Explain how will you modify the Newmark's equation based on Boussinesq's analysis for vertical pressure below a corner of uniformly loaded rectangular area when the point at which vertical pressure is required is not located below a corner but below some other point of the rectangle.
 - (d) Determine the vertical stress at a point P which is located 3 m below and at a radial distance of 3 m from the vertical load of 100 kN. use Westergaard's solution. ($\nu = 0.0$)

ECE011/DQJ-21196

1

[Turn Over]

- (e) A concentrated load of 40 kN acts on the surface of a soil. Determine the vertical stress increment at points directly beneath the load upto a depth of 5 m.
- (f) A water tower is supported only on three pillars forming an equilateral triangle with 10 m side. The total weight of the tower is 120 tonnes. Calculate vertical stress 10 m below the ground level under any one of the legs.
2. Attempt any **two** parts of the following : **(6×2=12)**
- (a) A foundation in sand will be 5 metres wide and 1.5 metres deep. Adopting a factor of safety of 2.5, what will be safe bearing capacity if the unit weight of the sand is 1.9 gm/c.c. and angle of internal friction is 35° . How does it compare with safe bearing capacity for surface loading.
 $N_c = 57$, $N_q = 44$, $N_y = 42$.
- (b) Determine the ultimate bearing capacity of the footing, 1.5 m wide and its base at a depth of 1 m, if the ground water table is located :
- at a depth of 0.5 m below the ground surface.
 - at a depth of 0.5 m below the base of the footing.
- $Y_{sat} = 20 \text{ kN/m}^3$.
 $Y_d = 17 \text{ kN/m}^3$, $\phi = 38^\circ$ & $c = 0$ use Terzaghi's theory. $N_q = 60$ & $N_y = 75$.
- (c) Explain in detail, the effects of size of footing on both the ultimate bearing capacity & the settlement.

3. Attempt any **two** parts of the following : (6×2=12)

- (a) What are the factors governing load carrying capacity of pile ? What is the objective of pile load test ? Write steps to determine safe load from pile load test.
- (b) What is negative skin friction ? What is its effect on the pile ? A 30 cm. diameter concrete pile is driven in a normally consolidated clay deposit 15 m thick. Estimate the safe load. Take $C_u = 70 \text{ kN/m}^2$, $\alpha = 0.9$ and F.S. = 2.5
- (c) Discuss the components of well foundation and draw the neat sketch of a well foundation. Explain all the terms in brief.

4. Attempt any **two** parts of the following : (6×2=12)

- (a) Derive an expression for the factor of safety of an infinite slope in a cohesionless soil. What is the effect of steady seepage parallel to the slope on the stability ?
- (b) A 10 m high cutting has a slope of 40° to horizontal, the soil was tested and its cohesion, void ratio & angle ϕ were found to be 2.5 t/m^2 , 0.81 and 14° respectively. Determine the FOS with respect to cohesion against failure of the slope. When water level rises upto the full height :

Given : $G = 2.7$ & for 40° slope values of stability number for different values of ϕ

| ϕ | N |
|------------|-------|
| 6° | 0.122 |
| 7° | 0.116 |
| 14° | 0.074 |

- (c) What are the design criteria for foundations of reciprocating machines based on IS : 2874 (I) - 1982 ? Discuss criteria for the design of foundation in case of free vibration without damping.